

Antisilikon-Lösung

8080

Wetting agent solution for solvent-based furniture coatings for **professional and industrial use**

PRODUCT DESCRIPTION

Product numbers

8080000210

General

Special solution for solvent-based furniture coatings to reduce surface tension. Effectively counteracts crater formation and can improve substrate wetting.

Application area

Additive for solvent-based coating systems in furniture and interior finishing.



PROCESSING

Processing instructions



- Please stir and shake the product well before use.
- The temperature of the product and object, and the room temperature must be at least +10 C.
- Antisilikon-Lösung (8080) must be incorporated carefully into the hardened varnish by stirring.
- Paints/varnishes that have been mixed can be used as explained in the relevant technical data sheet.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result.
- Please follow our **ARL 131 - Working guidelines for PUR furniture paints**.

Quantity to be added



Addition level: 0,1% - 1% to the coating.

The quantity to be added will vary according to the area of use and equipment used.

Therefore please contact your sales representative.

Cleaning the working equipment




8501

With Waschverdünner (8501) immediately after use.

ORDERING INFORMATION

Size of trading unit 500 ml

FURTHER DETAILS**Durability / storage**

Min. 1 year(s) in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Close opened containers well and use up the content as soon as possible.

Safety information

The product is only suitable for the industrial and professional use.

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at **www.adler-lacke.com**.