

## Aquawood Finatop 40

5140

Water-based, **silky gloss thick-coat glaze** for **wooden windows and exterior doors**, for use in industry and trade

Optimised for a **3-layer coating system**

### PRODUCT DESCRIPTION

#### General

Silky gloss, water-based, breathable thick-coat glaze with outstanding weathering resistance due to innovative, extremely long-lasting protective mechanisms against UV radiation. Stand-out features of this product include the highest degree of transparency, very good block resistance, very good impact strength, very rapid establishment of water resistance, short drying times and improved resistance to mechanical damage.

#### Special properties and standards



- **Proof of suitability according to DIN EN 927-2**  
Confirmed by an external test certificate.
- **ÖNORM EN 71-3**  
Safety of toys; migration of certain elements (free of heavy metals)
- **DIN 53160-1 and DIN 53160-2**  
Confirmed by an external test certificate.  
Perspiration and saliva-proof properties.
- **KOMO® product certificate**  
KOMO® certification 33392 based on BRL 0817 "Film-forming intermediate and top coat systems on wood".
- **AgBB-scheme 2018/2021 Committee for Health-related Evaluation of Building Products (AgBB)**  
When used properly in accordance with the technical data sheet, the product fulfils the requirements of AgBB scheme 2018/2021 Committee for Health-related Evaluation of Building Products (AgBB)
- **French ordinance DEVL1104875A**  
Marking of construction coating products for their emission of volatile pollutants: A+

#### Application area




For dimensionally stable timber components for exterior and interior use, such as e.g. wooden windows and front doors.

For humid rooms (e.g. indoor swimming pools) only with a special build-up.

For non-dimensionally stable timber components we recommend thin-film systems such as Lignovit Lasur (5315) or Pullex Plus-Lasur (4415).


## PROCESSING

### Processing instructions



- Please stir the product before use. However, prevent entry of air while stirring.
- The temperature of the product and object, and the room temperature must be at least + 15 °C.
- The optimal conditions for use are between 15 - 25 °C with a relative atmospheric humidity between 40 - 80 %.
- Too high dry film thicknesses from approx. 120 µm reduce the diffusion capacity and should thus be avoided.
- Sealants must be compatible with the coat and may only be applied once the paint has dried through. Sealing profiles with plasticizers tend to stick together in combination with paints. Please only use those types that have been tested.
- An intermediate coating with Aquawood Intermedio ISO (5705) is recommended to prevent air inclusions in deep-pored hardwood species and to avoid film interference on larch.
- When changing from Aquawood Finatop 40 (5140) to other water-based paint systems, care must be taken to adequately clean the pipes and spray equipment, preferably with warm water.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result. Deviations lead to film and adhesion problems as well as to impairments with regard to weathering and colour shade stability.
- Please follow our **ARL 300 - Working guideline for coating dimensionally stable and limited dimensionally stable construction elements - General part** along with all standards and guidelines for window construction.

### Application technique



|                                         | Airless       | Airless air-supported (Airmix®, Aircoat, etc.) |
|-----------------------------------------|---------------|------------------------------------------------|
| Spraying nozzle Ø (mm)                  | 0,28 – 0,33   |                                                |
| Spray nozzle (Ø inch)                   | 0,011 – 0,013 |                                                |
| Nozzle angle (°)                        | 20 – 40       |                                                |
| Spraying pressure (bar)                 | 80 – 100      |                                                |
| Atomising Air (bar)                     | -             | 0,5 – 1,5                                      |
| Spraying distance (cm)                  | 25            |                                                |
| Diluent                                 | Wasser        |                                                |
| Diluent amount added (%)                | 0 – 5         |                                                |
| Applied quantity per application (g/m²) | 225 – 300     |                                                |
| Wet film (µm)                           | 225 – 300     |                                                |
| Dry film complete coating system (µm)   | 80 – 120      |                                                |

The shape and surface condition of the workpiece as well as the type of application influence the actual consumption. Accurate values for consumption must be obtained by applying trial coats in advance.

**Drying times**

(at 23 °C and 50 % rel. humidity)




|                                                                                                                                                                            |                 |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| Dust-dry (ISO 1517)                                                                                                                                                        | ca. 1 hour(s)   |
| Tack-free                                                                                                                                                                  | ca. 2 hour(s)   |
| Stackable with PE fine foam spacers at room temperature                                                                                                                    | ca. 5 hour(s)   |
| Stackable with PE fine foam spacers after forced drying<br>20 minutes evaporation zone / dripping zone<br>90 minutes drying stage (35 – 40 °C)<br>20 minutes cooling stage | ca. 130 minutes |
| Recoatable                                                                                                                                                                 | ca. 12 hour(s)  |

The figures given above are reference values. The drying time depends on the type of substrate, coat thickness, temperature, air exchange and relative atmospheric humidity.

Lower temperatures and/or high level of atmospheric humidity can increase the drying time.

Avoid direct sunlight!

**Cleaning the working equipment**

With water immediately after use.

To remove dried paint residues we recommend using Clean Aqua-Cleaner (8029) (diluted 1:1 with water).

**SUBSTRATE****Type of substrate**

Wood in accordance with the guidelines for window construction.

**Substrate property**

The substrate must be dry, clean, capable of holding the paint, free from separating substances such as grease, wax, silicone, resin etc. and free from wood dust, as well as tested for suitability for coating.

**Wood moisture**

13 % ± 2 %

**COATING SYSTEM****General**

The following coating systems are exemplary.

KOMO-certified coating systems can be found under: <https://www.komo.nl/certificaten/33392/>

**Impregnation**

1 x Aquawood Primo (5453)

Intermediate drying: approx. 4 hour(s)

Use wood preservatives safely. Always read the label and observe the respective technical data sheets of the products before use.

Please follow our **ARL 056 - Working guideline for the use of wood preservatives**.

**Intermediate coat****Softwoods:**

1 x Aquawood Intermedio DQ (5706)

**Hardwoods and Larch:**

1 x Aquawood Intermedio ISO (5705)

Intermediate drying: approx. 2 hour(s)

|                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Intermediate sanding</b><br>              | Grit size 220 – 280<br>Remove sanding dust.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Finishing coat</b>                                                                                                         | 1 x Aquawood Finatop 40 (5140)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>For front doors</b>                                                                                                        | To achieve optimal chemical and mechanical resistance, an additional application of Aquawood Protect (5128) (colourless two-component clear coating) is recommended, or alternatively the use of the Aquawood Protor or Aquawood Dura system. Deviations from this system recommendation may lead to reduced surface resistance.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>MAINTENANCE</b>                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Care</b>                                                                                                                   | <p>The durability depends on several factors: these include particularly the type of weathering, constructive protection, mechanical stress and the choice of colour applied. To obtain long durability, regular inspection, maintenance and, if necessary, repair measures are necessary.</p> <p>Annual cleaning with Top-Cleaner (7208) and maintenance with Top-Care (7227) in the package with Windoor Care-Set (7229).</p> <p>Please follow our <b>ARL 304 - Working guideline for coating dimensionally stable and limited dimensionally stable construction elements - Maintenance and repair.</b></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>ORDERING INFORMATION</b>                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Size of trading unit</b>                                                                                                   | 5 kg, 25 kg, 120 kg poly drum                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Colour shades / Glosslevels</b><br><br> | <p><b>Standard colour(s):</b><br/> Frumento (5140055798)<br/> Canapa (5140053812)<br/> UV-Plus Chiaro (5140062628)<br/> UV-Plus Scuro (5140062629)<br/> Tanne (5140058707)<br/> Orzo (5140053825)</p> <p>Other colour shades can be obtained using the <b>ADLER colour mixing system ADLERMix.</b></p> <p><b>Base paint(s):</b><br/> Aquawood Finatop 40 Basis W30 (5140000030)</p> <p>The final colour is basically obtained from the inherent colour of the wood, the applied quantity, the colour of the impregnation and the colour of the finishing coat.</p> <p>In order to ensure uniformity of the colour shade, use only material with the same batch number on a given surface.</p> <p>It is recommended to prepare a trial colour sample on the original substrate using the coating system selected in order to assess the final colour shade.</p> <p>In order to lay particular emphasis on the wood structure, the colour shade of Aquawood Primo (5453) selected should be darker than the one of Aquawood Finatop 40 (5140).</p> <p>Please observe our <b>ARL 800 - Working guideline for working (including care and maintenance) with ADLER Mix, PUR Mix and Color4You dosing machines.</b></p> |

**Supplementary products**

Clean Aqua-Cleaner 8029 (8029)  
 Aquawood Intermedio DQ (5706)  
 Aquawood Intermedio ISO (5705)  
 Aquawood Primo (5453)  
 Aquawood Protect (5128)  
 Lignovit Lasur (5315)  
 Pullex Plus-Lasur (4415)  
 Top-Care (7227)  
 Top-Cleaner (7208)  
 Windoor Care-Set (7229)

Please refer to the corresponding technical data sheets of the products.

**FURTHER DETAILS****Durability / storage**

Min. 1 year(s) in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Close opened containers well and use up the content as soon as possible.

**Technical specifications**

VOC content of the ready-to-use mixture: Limit value according to Directive 2004/42/EC for Aquawood Finatop 40 (Cat A/e): 130 g/l.  
 Aquawood Finatop 40 contains a maximum of 30 g/l VOC.

**Giscode**

BSW20

**DGNB (German Sustainable Building Council)**

Quality level 4 (with factory coating)

**Safety information**

The product is only suitable for the industrial and professional use.

When sanding, use at least a P2 dust filter as personal safety equipment to protect against abrasive and wood dust. In case of hardwood (especially for Beech, Oak) a dust filter P3 is recommended.

The inhalation of paint aerosols during spray application must generally be avoided. This is ensured by the proper use of a respirator (combination filter A2/P2).

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at [www.adler-lacke.com](http://www.adler-lacke.com).