Technical data sheet



7081 Legno Dry

Additive for oils that dry by oxidation, for trade and industry

	PRODUCT DESCRIPTION
Product numbers	7081000210
General	Special solution to speed up the oxidative drying of oils, for trade and industry
Application area	Additive for selected oils from the Legno product range that dry by oxidation.

PROCESSING

after use.

Processing instructions







- Please stir and shake the product well before use.
- The temperature of the product and object, and the room temperature must be at least +10 C.
- Carefully stir Legno Dry (7081) into the oil.
- Oils that have been mixed must be used in accordance with the instructions in the relevant technical data sheet.
- Any change in the processing sequence, environmental conditions, nonobservance of instructions or the use of products not listed may have an unfavourable effect on the result.
- Please read and take note of our working guidelines ARL 013 Safety measures required for the use of oils and waxes that dry by oxidation and ARL 160 - Working guidelines for oils and waxes.

Quantity to be added



Depending on the surface treatment system being used, the quantity to be added will be between 1 and 3 % by weight.

The quantity to be added will vary according to the area of use and equipment used.

With Legno-Reiniger (7003) or Adlerol-Terpentinölersatz (7231) immediately

Therefore please contact your sales representative.

Cleaning the working equipment





1-1 IMC 7081 | 05/25 | replaces 1-0

	ORDERING INFORMATION
Size of trading unit	200 ml
	FURTHER DETAILS
Durability / storage	Min. 1 year(s) in the original sealed containers. Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).
Safety information	The product is only suitable for the industrial and professional use. Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at www.adler-lacke.com.