

Legno Hardener

7084

Solvent-free hardener to use as the second component for selected 2C products in the **Legno range**, for **industry** and **trade**

PRODUCT DESCRIPTION

Product numbers

7084000210

General

Solvent-free, monomer-reduced hardener formulated from an aliphatic polyisocyanate.

Application area



Hardener component for selected oils in the Legno product range that dry by oxidation, for furniture and interior finishing, as well as for wooden floors, staircases and interior doors.

Please refer to the corresponding technical data sheets of the products.

PROCESSING

Processing instructions

- Carefully mix in the Legno Hardener (7084) immediately after adding to the oil component.
- Oils that have been mixed must be used in accordance with the instructions in the relevant technical data sheet.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result.
- Please read and take note of our working guidelines **ARL 013 – Safety measures required for the use of oils and waxes that dry by oxidation** and **ARL 160 – Working guidelines for oils and waxes**.


ORDERING INFORMATION

Size of trading unit

0.3 l, 1 l

FURTHER DETAILS

Durability / storage



Min. 6 month(s) in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Immediately seal the container to prevent humidity from penetrating.

Safety information



The product is only suitable for the industrial and professional use.

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at **www.adler-lacke.com**.
