Technical data sheet



9073 Legno Mix

Pigment concentrates for Legno Smart-Öl (7045) for use in trade and industry.

	PRODUCT DESCRIPTION
General	Pigment concentrates for Legno Smart-Öl (7045) for use in trade and industry, with very good lightfastness, a high degree of accuracy as regards colour and colour strength, and a high yield.
Application area	For tinting Legno Smart-Öl (7045).

PROCESSING

Processing instructions













- Please stir and shake the product well before use (1 minute shaker).
- The temperature of the product and object, and the room temperature must be at least +10 C.
- The product is ready to use.
- Do not use the product as a coating!
- Use only in combination with the base materials recommended by ADLER.
- Coating systems that have been carefully mixed with Legno Mix (9073) can be used as described in the relevant Technical Data Sheet.
- The product dries through oxidation and can tend to form a skin if left to stand for extended periods. Opened containers should be used up as quickly as possible.
- Any change in the processing sequence, environmental conditions, nonobservance of instructions or the use of products not listed may have an unfavourable effect on the result.
- Please read and take note of our working guidelines ARL 013 Safety measures required for the use of oils and waxes that dry by oxidation and ARL 160 - Working guidelines for oils and waxes.

Cleaning the working equipment





7231

With Legno-Reiniger (7003) or Adlerol-Terpentinölersatz (7231) immediately after use.

ORDERING INFORMATION

Size of trading unit

11

1-1 IMC 9073 | 04/25 | replaces 1-0

Colour shades / Glosslevels

Standard colour(s):
Weiß W (9073090550)
Oxidgelb OY (9073090551)
Oxidrot OR (9073090552)
Schwarz S (9073090553)

Adlerol-Terpentinölersatz (7231)
Legno Reiniger (7003)
Please refer to the corresponding technical data sheets of the products.

FURTHER DETAILS

Durability / storage

Min. 1 year(s) in the original sealed containers.

Safety information

The product is only suitable for the industrial and professional use.

i

When using cloths that have been soaked with oxidative drying products, there is a risk of spontaneous combustion! Spread soaked cloths out and let them dry; it is necessary to store them in sealed metal containers or under water

Using the product in spraying booths, which are contaminated with nitrocellulose-containing spray dust, is prohibited owing to the risk of self-ignition!

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at **www.adler-lacke.com**.