

Aquafix E

8128

Additive for Bluefin Pigmocryl NG for professional and industrial use

PRODUCT DESCRIPTION

Product numbers

8128000210

General

Colourless, water-based additive for Bluefin Pigmocryl NG when used in build-ups that require high elasticity (e.g. stair treads).

Application area



For furniture, interior fixtures, wall paneling and wood ceilings.
For professional and industrial coating of stair treads.

PROCESSING

Processing instructions



- Please stir the product before use.
- Carefully stir Aquafix E (8128) into the undiluted coating; afterwards stir in the required amount of thinner.
- Aquafix E (8128) leads to a noticeable increase in the gloss level of the base coating.
- Mixed paints must be processed as specified in the corresponding technical data sheet.
- The processing properties of the products are preserved.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result.

Quantity to be added


20 % by weight on coating



Drying times

(at 23 °C and 50 % rel. humidity)

The drying behaviour of the coating system is not affected by the addition of Aquafix E (8128).

Cleaning the working equipment

With water immediately after use.

To remove dried paint residues we recommend using Clean Aqua-Cleaner (8029) (diluted 1:1 with water).

ORDERING INFORMATION**Size of trading unit**

800 g

FURTHER DETAILS**Durability / storage**

Min. 1 year(s) in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Close opened containers well and use up the content as soon as possible.

Safety information

The product is only suitable for the industrial and professional use.

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at **www.adler-lacke.com**.
