

Pigmolux-Fluid

8048

Special additive for Pigmolux coatings for industrial use

PRODUCT DESCRIPTION

Product numbers

90773

General

Special solution for Pigmolux DC for the reduction of surface tension. Effectively counteracts crater formation and can improve substrate wetting without reducing viscosity.

Application area

Additive for water-based coatings for furniture and interior finishing.



PROCESSING

Processing instructions



- Please shake / stir the product before use.
- The temperature of the product and object, and the room temperature must be at least + 15 °C.
- Mix Pigmolux-Fluid (8048) carefully into the paint/varnish while stirring continuously.
- Adding Pigmolux-Fluid (8048) may lead to a reduction in chemical resistance and overall hardness.
- The drying behaviour of the coating system is slightly changed by the addition of Pigmolux-Fluid (8048).
- Paints/varnishes that have been mixed can be used as explained in the relevant technical data sheet.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result.
- Please follow our **ARL 150 - Working guidelines for water-based furniture coatings**.

Quantity to be added



Quantity to be added: 0.1% - 5% relative to the quantity of paint or varnish.

The quantity to be added will vary according to the area of use and equipment used.

Therefore please contact your sales representative.

Cleaning the working equipment

8029

With water immediately after use.

To remove dried paint residues we recommend using Clean Aqua-Cleaner (8029) (diluted 1:1 with water).

ORDERING INFORMATION**Size of trading unit**

750 g, 5 kg, 25 kg

FURTHER DETAILS**Durability / storage**

Min. 1 year(s) in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Close opened containers well and use up the content as soon as possible.

Safety information

The product is only suitable for industrial use.

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at **www.adler-lacke.com**.
